


NORAXON



NiNOX™ Camera Systems

High-Speed, High-Definition, Portable



USB 3.0
Color
120/300 FPS

EMG

3D MOTION

SOFTWARE

PRESSURE/FORCE

VIDEO ANALYSIS

NiNOX™ Camera Systems

Versatile High-Performance, Plug-and-Play Video Capture and Analysis Solution

The NiNOX camera system is a high-speed, high-definition, automatically synchronizing small form factor piece of equipment, that provides a portable video option for high-speed video analysis.



NiNOX 120

For crisp synchronized reference video

GENERAL

- Size: 1.15" x 0.8" x 4.42"
[29.1 x 20.3 x 112.4 mm]
- Weight: 0.6 lb. [273 g]
- Housing material: anodized aluminum
- Built-In USB 3.1 & Sync Cables
- Standard Windows Camera Driver
- On-Board MJPEG Compression
- Auto Focus & White Balance
- Constant Field of View
- Digital Zoom

| FPS | Resolution |
|-----|---------------------------|
| 60 | 1920 x 1080 or 1280 x 720 |
| 120 | 640 x 480 |



* Minimum computer technical specs required.

The Noraxon name, logo, myoRESEARCH and Ultium are registered trademarks. myoANALOG, myoFORCE, myoMETRICS, myoMOTION, myoMUSCLE, myoPRESSURE, myoVIDEO, myoSYNC, forZe, NiNOX and TRUsync are common-law trademarks of Noraxon USA. (C) 2019, all rights reserved. All other trademarks remain the property of their respective owners.

Powerful myoVIDEO™ Analysis Software

The accompanying software analysis module, myoVIDEO™, streamlines the entire video data capture and analysis process. Software features include:

- 2D video analysis toolset
- Slow motion playback
- Automatic marker-tracking (300c only)
- Integration into customizable reports



NiNOX 300c - includes the choice of 1 lens

For marker tracking & high-speed video analysis

GENERAL

- Size: 2.13" x 2.19" x 1.96"
[54 x 74 x 70 mm]
- Weight: 0.7 lb. [325 g]
- Low light color image sensor
- USB 3.0 powered
- GPIO Sync
- Housing material: anodized aluminum
- Supports up to 4 cameras

BUILT-IN LED

- Neutral white light at 4000 Kelvin
- Keypad-controlled intensity up to 350 lumens
- Optimized for marker tracking

| FPS | Resolution |
|-----|-------------|
| 30 | 1920 x 1080 |
| 60 | 1280 x 1080 |
| 100 | 960 x 720 |
| 250 | 640 x 480 |
| 300 | 480 x 340 |

| Lens Options | Field of View | |
|--------------|---------------|---------|
| SIZES | 30 FPS | 300 FPS |
| 3.5 mm | 76 | 21 |
| 12 mm | 27 | 7 |